



NDL Industries

**APPLICATIONS**

Commercial, Industrial, and Residential HVAC and Refrigeration

# CO<sub>2</sub> Copper Fittings

The NDL CO<sub>2</sub> copper fittings (C19400 high-pressure copper) are specifically designed for use in CO<sub>2</sub> Refrigeration and HVAC systems. An industry leader with our copper fittings, we exceed industry standards for working pressure.



## We've received UL Certification for our CO<sub>2</sub> Copper Fittings

Our entire selection of CO<sub>2</sub> Copper Fittings have recently received **UL Certification!** As an industry leader with our Copper Fittings, we plan to keep consistently outdoing ourselves in quality and service. With zero reported failures since 1999, and the quality of our fittings consistently being one step ahead of the competition; we're here to fit your needs.



# CO<sub>2</sub> Copper Fittings

## Technical Data

SIZE RANGE	From 3/8" up to 2-1/8"
MATERIAL	Copper alloy CuFe2P C19400
OPERATING TEMPERATURE	-196°C to 150°C / -320°F to 302°F
BURST PRESSURE	>390 bar / >39 MPa / >5656 psi
MAXIMUM OPERATING PRESSURE	130 bar / 13 MPa / 1885 psi at 150°C
APPLICATION	Air conditioning and refrigeration. Designed for high-pressure applications, especially for CO <sub>2</sub> (R744) systems.
TUBE COMPATIBILITY	Compatible with main pipe types manufactured from copper iron alloys available on the market.

## Specifications

- Our high-pressure copper-iron alloy fittings are tested for actual burst pressure with the results exceeding 3 times the design pressure.
- Each fitting is marked with "CO<sub>2</sub> 130 BAR" and OD size for easy field identification.
- Our 1-Year Warranty proves that we have confidence in our fittings, and that they can be trusted in the field.
- Our fittings have zero reported failures since 1999.
- NDL ensures copper quality content and strict adherence to meet or exceed ASME B16.22 standards for wall thickness.
- The fittings have tight tolerances on the cup side for a stronger joint with the tube and easier brazing.
- Fittings are poly-bagged within the box, keeping them clean and contaminant-free prior to installation.

## How we discovered the need for CO<sub>2</sub> Service Tees

When working with CO<sub>2</sub> refrigeration systems, it's important to consider the high-pressure levels involved. Access ports commonly used in regular refrigeration systems may not be suitable for use with CO<sub>2</sub> systems, as the Schrader valve seal can break under pressure, necessitating the venting of the entire line.

To avoid this issue, it is recommended to use a service valve that can be closed, enabling workers to easily connect and disconnect equipment as needed. While installing a service valve may require more time upfront, it is generally preferred by workers who regularly service equipment.

Our Tee fittings are designed specifically for the installation of service valves, streamlining the process and ensuring a secure, leak-free seal. By using a service valve and our specialized fitting, you can prevent high-pressure problems and make your work more efficient.



Explore our full line of high-quality HVAC-R and plumbing products.

ndlinc.com | 1-866-635-6888 | sales@ndlinc.com

@ndlindustries

